

indiana line

BASSO





I modelli Basso sono subwoofer attivi dal sorprendente impatto acustico, nati per completare l'estensione alle basse frequenze dei diffusori utilizzati negli impianti hi-fi e nei sistemi home cinema. I loro amplificatori sono dotati di una sezione controlli molto completa, che consente una perfetta interfaccia con gli altri componenti dell'impianto audio e con l'ambiente d'ascolto. Il design pulito e raffinato dei mobili e le compatte dimensioni rendono agevole il loro inserimento in ogni ambiente.



Basso are active subwoofers with astonishing acoustic impact, they are suitable to complete the low frequency extension for stereo hi-fi or home cinema systems. Their amplifiers feature a very complete control section, which allows a perfect interface with the other components of the audio system and with the listening room. The clean and elegant design of the enclosures makes placement easy with any kind of furnishing.

BASSO 942

active subwoofer
 220 mm speaker diameter
 275 mm passive radiator
 D-Class amplifier
 250 watt nominal power
 400 watt max power
 25 ÷ 180 hertz frequency response
 40 ÷ 180 hertz crossover frequency
 220 ÷ 240 volt power supply
 300 watt max power consumption
 <0.5 watt stand-by consumption
 310 x 335 x 345 mm - 13.7 kg

• finishing: BLACK high gloss



**BASSO 840**

active subwoofer
 275 mm speaker diameter
 twin reflex port
 AB-Class amplifier
 75 watt nominal power
 125 watt max power
 30 ÷ 180 hertz frequency response
 40 ÷ 180 hertz crossover frequency
 220 ÷ 240 volt power supply
 125 watt max power consumption
 <0.5 watt stand-by consumption
 300 x 320 x 385 (h) mm - 10.2 kg

• finishing: *BLACK matt vinyl*

**BASSO 922**

active subwoofer
 275 mm speaker diameter
 twin reflex port
 AB-Class amplifier
 75 watt nominal power
 125 watt max power
 29 ÷ 180 hertz frequency response
 40 ÷ 180 hertz crossover frequency
 220 ÷ 240 volt power supply
 125 watt max power consumption
 <0.5 watt stand-by consumption
 310 x 330 x 335 (h) mm - 9.8 kg

• finishing: *WHITE high gloss*

**MIO SUB**

active subwoofer
 178 mm speaker diameter
 twin reflex port
 AB-Class amplifier
 50 watt nominal power
 80 watt max power
 40 ÷ 180 hertz frequency response
 40 ÷ 180 hertz crossover frequency
 220 ÷ 240 volt power supply
 80 watt max power consumption
 <0.5 watt stand-by consumption
 230 x 250 x 255 (h) mm - 5.9 kg

• finishing: *BLACK matt vinyl*